


Nitrile Coated 15 ga. Nylon


PRODUCT DETAILS


- + 15 ga. nylon shell
- + Foam nitrile palm coating w/smooth finish
- + Elastic knit wrist w/hemmed cuff




HAZARD SOLUTIONS

 Abrasion Resistant

 Heat Resistant

 Tear Resistant


FEATURES


 Breathable


 Dexterity

 Solid Grip

RATINGS

 Conductive Heat Level 1, Up to 176° F/80° C (ANSI/ISEA 105-2016)

 EN 388 - 4131X

 EN 407 - X1XXXX

CFIA

SIZES

ITEM #	SIZE UPC
99-1-9860-7	S (7) 063344175360
99-1-9860-8	M (8) 063344175377
99-1-9860-9	L (9) 063344175384
99-1-9860-10	XL (10) 063344175391
99-1-9860-11	X2L (11) 063344257448

*Not all styles/sizes available in all regions.

PACKAGING

- + 12 PR per Polybag 120 PR per Carton
- + Vend Pack Option Available: Yes

*Bob Dale Gloves products are tested for cut and puncture resistance. These products ARE NOT CUT AND PUNCTURE PROOF. Do not use with moving blades, tools or serrated blades.
*Not Proposition 65 compliant.